



INDY-606 Single Unit 6'3" H x 6'L x 29" W Platform Height 1-6 ft 149 lbs.

Indy Scaffolds are interchangeable with Perry & Sonny Scaffolds INDY-606 Single Unit 6'3" H x 6'L x 29" W Platform Height 1-6 ft 149 lbs.

INDY-GRT 6' Guard rail set w/ toe board 72 lbs.



User friendly squeeze-lock is spring loaded to maintain the locked position at all times except when released for adjustment. A locking knurled knob is provided to prevent unintentional release. Additional snap pin is provided as a dual locked scaffold system.



Four platform alignment pins provide a positive and secure fit for the work platform. Adjustment of the work platform is possible without disassembling the scaffold unit.



Steel edge banding protects all four sides of the exterior-grade plywood work platform without using rivets, screws or staples. Hand holds on each side provide ease in handling. Platform is held in place with spring-loaded retaining clips.



INDY-606

Single Unit (2 Units shown stacked) 12" H x 6'L x 29" W Platform Height 2-12 ft 298 lbs. (2 Units)

INDY-GRT

6' Guard rail set w/ toe board (End guard rail panels not used in this application) 72 lbs.

INDY-ORP 4 Piece Outrigger Set 27 lbs.

> Maximum Capacity 1000 lbs. Distributed

Meets or Exceeds Requirements of American National Standards Institute ANSI CODE A 10.8

Meets or Exceeds OSHA Requirements


Patent No's 6,471,003 6,761,247



4" x 4" Baseplates provide a solid foundation for scaffolds in areas where casters can't be safely used. Great for use on stairways.



5" swivel casters with dual brakes that prevent both rolling and swiveling when brake lever is depressed. Caster stem includes compression ring and a 2" snap pin to attach the caster to the scaffold.



Use 4 outriggers on Indy Scaffolds above 6' high. Outrigger includes 2 snap pins and 1 thumb screw. Casters and base plates sold separately.

MORE GREAT ITEMS TO GET THE JOB DONE.





595 E. Lugbill Road Archbold, Ohio 43502 877-447-2648 www.GraniteInd.com