PRODUCT SPECIFICATIONS

444ASZ Shock Absorbing Lanyard

Product Description

This dual-leg tubular-elastic web lanyard with shock absorbing pack limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

Product Features

- 1-3/16" synthetic webbing with shock pack
- Stretches to minimize tripping and snagging hazards
- Standard 6' length relaxes to 4.5' when not stretched
- Z136 locking snaphooks on each end (2-2/2" gate opening)
- Additional snaphook options available

MATERIAL SPECIFICATIONS	
Webbing	1-3/16" polyester webbing, min tensile strength 6,000 lbs.
Core	1" Elastic cord
Hardware	Z74 locking snap: Zinc plated alloy steel, 3/4" gate opening,
	proof loaded 3,600 lbs, min tensile strength 5,000 lbs
	Z136 rebar snaps: Zinc plated alloy steel, 2-1/2" gate opening,
	proof loaded 3,600 lbs, min tensile strength 5,000 lbs

PERFORMANCE SPECIFICATIONS	
Lanyard Class	6' Free fall
Arrest Force	900 lbs
ANSI User Capacity	130 to 310 lbs
OSHA User Capacity	400 lbs

RELEVANT STANDARDS	
ANSI	Z359.1
OSHA	Meets or exceeds OSHA requirements

SIZES/LENGTHS
Standard length of 6 feet. Other sizes may be available.

100 N 13th St. • Franklin PA • 16323
877.228.9327 • 814-437-1808
frenchcreekproduction.com

WARNING: Read, understand and follow all labels and instructions prior to use, Inspect before each use. Remove from service if there is evidence of damage or excessive wear